



---

## Wardiam PRO Center



---

### Features

Triple redundancy for outbound communications; Ethernet, WIFI and 2G/3G  
Wireless RF connectivity for up to 32 peripheral devices  
Built in RF and 2G/3G jamming detection  
Dual tamper protection (opening and connections)  
Capacitive touch keypad with backlight  
Desk or wall installation  
Support with embedded bubble level

---

### Dimensions

140 x 30 mm (diameter x height)

### Weight

250 grams

---

### Wireless communications

Sub-1 GHz (433/868/915 MHz) up to 50m range  
2G/3G - 850/900/1800/1900/2100 MHz  
Wifi 802.11 b/g/n

---

### Connectivity

Ethernet  
Web/iOS/Android management apps  
Compatible with Central Monitoring Stations (CSM) using ADEMCO contact ID

---

### Power supply and autonomy

5V power supply input  
12h autonomy internal backup rechargeable battery

---

### Environmental requirements

Working temperature: 0 - 35 °C  
Storage temperature: -20 - 45 °C

---

### Certifications

CE/UL/Grade 2

---

Optional peripheral devices

- Wireless Detector
- Wireless still Camera
- Wireless Alarm Siren

Box contents

- Control central
- 5V power supply
- Wall mounting support
- Optional adhesive pads for wall mounting
- Documentation

